



## Features / Benefits

- Refrigerant R134A
- High-efficiency coaxial tube in tube evaporators
- Advanced digital controller with diagnostic and storage alarms
- Single phase and three phase models available
- Non ferrous water circuit
- Scroll compressors



## Product Specifications

CAPACITIES		0006	0010	0015	0023	0029	0034	0061
Cooling Capacity	ton	0.6	1.0	1.5	2.3	2.9	3.4	6.1
Capacity based on 60°F water outlet temp.; 10°F delta t @ 95°F ambient temperature								
BTU/hr		7,019	11,786	18,287	27,640	34,416	40,587	75,756
Reservoir Capacity	gal	5.25	5.25	14.5	14.5	14.5	21	21
Comp/Circuits/Fans		1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1

DIMENSIONS		0006	0010	0015	0023	0029	0034	0061
Length	in	31	31	29	29	29	39	39
Width	in	23	23	26	26	26	30	30
Height	in	18	18	44	44	44	51	51
Weight (Dry)	lbs	169	176	315	326	355	507	529

ELECTRICAL		0006	0010	0015	0023	0029	0034	0061
Volts		230	230	460	460	460	460	460
Phase		1	1	3	3	3	3	3
Hertz		60	60	60	60	60	60	60
FLA		9.9	14.7	7.4	8.6	11.5	12.0	16.6

MISC SPECS		0006	0010	0015	0023	0029	0034	0061
Refrigerant		R134A	R134A	R134A	R134A	R134A	R134A	R134A
Head Pressure	psi	65	65	75	75	75	70	65
Flow, Nominal	gpm	1.5	2	4	5	6	8	13
Fluid Connections	MPT	1/2"	1/2"	3/4"	3/4"	3/4"	1"	1"