



Features / Benefits

- Refrigerant 410A
- Precise temperature control for any industrial application
- Electronic expansion thermostatic valve
- Separated compressor compartment with removeable panels
- Refrigerant high and low pressure gauges



Product Specifications

CAPACITIES		0532	0598	0756	0946	1060
Cooling Capacity	ton	53.2	59.8	75.6	94.6	106
Capacity based on 45°F water outlet temp.; 10°F delta t @ 95° ambient temperature						
BTU/hr		638,070	717,480	907,629	1,135,901	1,272,728
Reservoir Capacity	gal	132	132	132	200	200
Compressors/Circuits/Fans		4/2/4	4/2/4	4/2/4	4/2/6	4/2/6

DIMENSIONS		0532	0598	0756	0946	1060
Length	in	124	124	124	175	175
Width	in	87	87	87	87	87
Height	in	95	95	95	95	95
Weight (Dry)	lbs	5,747	5,908	6,029	7,835	7,935

ELECTRICAL		0532	0598	0756	0946	1060
Volts		460	460	460	460	460
Phase		3	3	3	3	3
Hertz		60	60	60	60	60
FLA		196.0	227.0	257.0	315.0	365.0

MISC SPECS		0532	0598	0756	0946	1060
Refrigerant		R410A	R410A	R410A	R410A	R410A
Head Pressure	psi	40	40	40	40	40
Flow, Nominal	gpm	125	145	180	225	250
Fluid Connections	M Vic	3"	3"	3"	4"	4"